




TJN



TJN WITH OUTER CASING



TJN IN WHITE, SIMILAR TO RAL 9010



SWIRL UNIT AND CAP FOR THROW DISTANCE REDUCTION



DISCHARGE ANGLE INDICATOR

## TYPE TJN


ACOUSTICALLY AND TECHNICALLY OPTIMISED, FOR INSTALLATION IN WALLS AND ON RECTANGULAR AND CIRCULAR DUCTS, ADJUSTABLE – MADE OF PLASTIC

The new TJN jet nozzle offers improved acoustic properties and is also more energy-efficient

- Nominal sizes: 160, 200, 250, 315 and 400 mm
- Volume flow rate range 20 – 1000 l/s or 72 – 3600 m<sup>3</sup>/h
- Visible parts made of high-grade polymer in RAL white aluminium or pure white
- Optimised nozzle contours
- Discharge angle indication, discharge angle limiting and setting from – 30 to +30° on a concealed scale
- Easy to remove face cover ring with bayonet fixing

### Optional equipment and accessories

- 5 nominal sizes, each with a circular spigot or, as an option, with a connection piece for circular or rectangular ducts
- Swirl unit with acoustically optimised air control blades with unique saw tooth edges and cap for two-step reduction of the throw distance
- External electric actuator of compact height
- Electric actuator allows for integration with the central BMS
- Internal thermal actuator with shape memory alloy for the self-powered adjustment of the discharge angle
- All variants also available with outer casing



**THERMAL ACTUATOR  
WITH SHAPE MEMORY  
ALLOY**

## Application

---

### Application

- Type TJN jet nozzles for supply air discharge, with a long throw distance
- For production halls, gymnasiums, theatres and conference rooms as well as for large internal spaces in airports, railway stations and shopping centres
- Attractive design element for building owners and architects with demanding aesthetic requirements
- For supply air to room air temperature differences from  $-12$  to  $+20$  K
- Adjustable discharge angle, from  $-30$  to  $+30$  °, for switching between heating and cooling mode
- For push fitting directly onto circular ducts or as a branch off circular or rectangular ducts

### Special characteristics

- Easy to remove face cover ring with bayonet fixing
- Swirl unit with acoustically optimised air control blades with unique saw tooth edges and cap for two-step reduction of the throw distance
- Discharge angle indication, discharge angle limiting and setting from  $-30$  to  $+30$  ° on a concealed scale
- Electric or thermal actuator as options

### Nominal sizes

- 160, 200, 250, 315, 400 mm

## Description

---

### Variants

#### Connection

- For circular ducts (direct connection)
- K: For rectangular ducts
- R: For circular ducts

#### Actuator

- Manual adjustment
- E\*: Electric actuator
- T1: Thermal actuator

#### Parts and characteristics

- Nozzle with acoustically optimised contours and adjustable discharge angle (from –30 to +30°, in increments of 5°)
- Flange with position indicator (scale) and adjustable end positions, concealed by a face cover ring
- Spherical nozzle casing with spigot
- Outer casing (optional)
- Connection piece for circular and rectangular ducts (optional)
- Actuator (optional)

#### Attachments

- C: Outer casing

#### Accessories

- Swirl unit and cap for throw distance reduction

#### Useful additions

- TDC temperature difference control module

#### Construction features

- Spigot suitable for circular ducts to EN 1506 or EN 13180
- Spigot with double lip seal

#### Materials and surfaces

- Flange, face cover ring, swirl unit and cap made of ABS plastic, UL 94, V-0, flame retardant
- Spherical nozzle casing made of galvanised sheet steel
- Connection pieces for circular or rectangular ducts made of galvanised sheet steel
- Double lip seal made of rubber
- Exposed surface is pure white, similar to RAL 9010
- S1: White aluminium, similar to RAL 9006

#### Standards and guidelines

- Sound power level of the air-regenerated noise measured according to EN ISO 5135

#### Maintenance

- Maintenance-free as construction and materials are not subject to wear
- Inspection and cleaning to VDI 6022

#### Lindpro AB

---

□

Berglundavägen 12C  
SE-70236 Örebro  
SVERIGE  
Tel.: +46 (0) 19 12 37 40  
Mobil: 070-587 27 25  
Email: [larsgoran@lindpro.se](mailto:larsgoran@lindpro.se)

#### Online tjänster

---

› [Kontakta oss](#)

---

#### Service

---

Lindpro AB

Tel.: +46 (0) 19 12 37 40

Mobil: 070-587 27 25

Email: [larsgoran@lindpro.se](mailto:larsgoran@lindpro.se)